

DRAIN UNITS - GRAVITY COLLECTION



Gravity collection with pressure discharge. Discharge is done through a 1,5 m hose pressurizing the unit at 0,5 bar (3.5 psi). Includes a safety valve to avoid over pressurization.

372 400, 100 litres gravity waste oil drainer. Pressure discharge

373 400, 70 litres gravity waste oil drainer. Pressure discharge

Gravity collection with pump discharge. Discharge is done through a 1:1 pressure ratio pneumatic piston pump attached to the back of the unit reservoir and 1,5 m hose with a hydraulic type coupler.

372 200, 100 litres gravity waste oil drainer. Pump discharge

373 200, 70 litres gravity waste oil drainer. Pump discharge

Gravity collection with remote pump discharge. Discharge is done connecting the unit to a wall mounted discharge pump kit through a hydraulic coupler located at the bottom of the reservoir.

372 300, 100 litres gravity waste oil drainer. Remote pump discharge

373 300, 70 litres gravity waste oil drainer. Remote pump discharge

USED FLUID COLLECTION UNITS - SPECIALTY DRAINERS



Low level mobile drainers for gravity collection of waste oil and used automotive fluids such as antifreeze solutions. Recommended to use when a hoist or a service pit is not available. Gravity discharge through a drain valve or using an evacuation pump kit (PN 559 100) through a dry break hydraulic connector (PN 950 352) (not included).

435 000 Low level mobile drainer, 20 litres

20 litres (5.2 gallons) unit for use with passenger cars and small vans.

436 000 Low level mobile drainer, 95 litres

95 litres (25 gallons) unit for use with passenger cars, vans, tractors, commercial vehicles, etc.

436 100 Anti-freeze recovery unit

Low level-waste oil drainer 436 000 equipped with a DF50 diaphragm pump. Allows draining the antifreeze when a pit or lift is not available. Thanks to the diaphragm pump and the delivery gun is possible to reuse the antifreeze.

439 100 Pit rolling drainer, 95 Litres

Rolling drainer for being installed between pit rails with minimum / maximum width of 1.040 / 1.450 mm. 95 litres (25 gallons) capacity. Unit includes anti splash grid, four vertical and four horizontal rollers for easy rolling and an 1-1/4" outlet with ball valve. The unit allows the connection of a hydraulic connector for discharging the unit once full with a discharge pump kit.